

## FEATURES

- GBC was designed with solid lead plated and gelled electrolyte technology.
- A deep-cycle lead-acid battery is designed to deliver a maximum capacity and cycles as discharging.
- High temperature stability, mechanical strength and low acid displacement.
- Superior performance with deep discharges.
- Patented safety valve to have accurate pressure operating for long battery life.

## APPLICATIONS

- Golf Cars
- Power Wheelchairs
- Floor Sweepers
- Recreational Vehicle (RV)
- Renewable Energy



## SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	135 Ah @ 5 hour rate F.V.(1.70V/cell)
Approx. Weight	55Kg(121.3lbs.)
Terminals	B9 (Fitting M8 bolt & nut) I3 is optional
Internal Resistance	≤5.0m Ω (Fully Charged )
Max. Discharge Current	800 A (5 sec.)
Max. Charge Current	27.0 A
Self Discharge	< 2% per month (25°C)
Operating Temperature Range	-20°C~55°C(-4°F~131°F)
Container Material	Standard: ABS( UL94 HB) GBC 12/135 Optional: Flame Retardant ABS(UL94 V-0) GBC 12/135FR



DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> <li>■ Length 522±2.0 (20.55±0.08)</li> <li>■ Width 202±2.0 (7.95±0.08)</li> <li>■ Container Height 216±2.0 (8.50±0.08)</li> <li>■ Total Height 219.5±2.0 (8.64±0.08)</li> </ul>		<ul style="list-style-type: none"> <li>● Terminal B9</li> <li>● Terminal I3</li> </ul> <p>[M8 BOLT &amp; NUT] [M8 BOLT]</p> <p>Terminal Hardware Initial Torque: B9,I3(10.0Nm±5%)</p>

Constant power discharge characteristics at 25 °C/77 °F							Unit: W
F.V. (V/cell) \ Discharge Time	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr	
1.80V	1678	994	430.7	316.1	166.3	88.6	
1.75V	1704	1022	437.6	320.8	169.9	88.9	
1.70V	1716	1046	442.5	323.6	171.4	90.7	
1.65V	1720	1056	447.2	324.9	172.0	90.8	
1.60V	1723	1067	449.6	325.7	172.3	90.9	

Constant current discharge characteristics at 25 °C/77 °F							Unit: A
F.V. (V/cell) \ Discharge Time	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr	
1.80V	136.5	83.8	35.89	26.36	13.86	7.38	
1.75V	138.4	86.4	36.45	26.76	14.16	7.39	
1.70V	139.3	88.3	36.86	27.00	14.29	7.56	
1.65V	141.0	89.4	37.26	27.13	14.33	7.58	
1.60V	142.1	89.8	37.46	27.19	14.36	7.61	

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.