

FEATURES

- GBS delivers long cycle life and prolong life in elevated ambient temperatures.
- The generated heat can easy flow to the case walls because the whole volume of the cell is filled with gel.
- The immobilization of the electrolyte in the gel makes acid stratification impossible.
- Maintenance free(no water topping-up required).
- Low self-discharge rate, lower than 2% capacity loss per month.
- A small distribution of the special valve opening and closing pressure is important for a good (cycle) life time of the battery.

APPLICATION

- Solar power stations
- Telecommunications installations
- Traffic lights
- Street lightening
- Wind power



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	130Ah @ 100 hour rate F.V.(1.80V/cell)
Approx. Weight	40Kg(88.18lbs.)
Terminals	I2
Internal Resistance	≤7mΩ (Fully Charged)
Max. Discharge Current	800 A (5 sec.)
Max. Charge Current	26 A
Operating Temperature Range	-20°C~55°C(-4°F~131°F)
Container Material	Standard: ABS(UL 94-HB) GBS 12/130 Optional: Flame Retardant ABS(UL 94-V0) GBS 12/130FR

WSE ISO9001	UL MH19884
WSE ISO14001	CE C-AM20310-2474-E-16
WSE OHSMS	
<ul style="list-style-type: none"> ● IEC 61427-2005 ● GB/T 22473-2008 	

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> ■ Length 344±2.0 (13.54±0.08) ■ Width 172±2.0 (6.77±0.08) ■ Container Height 263.8±2.0 (10.39±0.08) ■ Total Height 280.3±2.0 (11.04±0.08) 		<ul style="list-style-type: none"> ● Terminal I2 <p>Terminal Hardware Initial Torque: 5.5Nm±5%</p>

Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr	100 Hr	120 Hr
1.85V	822.3	345.0	246.0	137.0	70.68	15.50	12.96
1.80V	830.2	352.2	248.8	138.0	70.92	15.60	13.03
1.75V	845.6	358.0	251.0	138.0	72.00	15.72	13.15
1.70V	855.7	360.0	252.0	139.3	72.24	15.84	13.27
1.65V	864.3	373.3	252.8	139.5	72.38	15.85	13.27

Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr	100 Hr	120 Hr
1.85V	68.2	28.7	20.50	11.39	5.89	1.29	1.08
1.80V	69.8	29.3	20.73	11.50	5.91	1.30	1.09
1.75V	71.1	29.8	20.92	11.58	6.00	1.31	1.10
1.70V	72.0	30.0	21.00	11.61	6.02	1.32	1.11
1.65V	72.7	31.1	21.07	11.63	6.03	1.32	1.11

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.