

VRLA Rechargeable Battery

MPL90-12

Handle Type



FEATURES

- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Low self-discharge rate,lower than 3% capacity loss per month
- Can be used in any orientation(excluding used inverted)
- The battery is designed with very lower resistance and exceeding high power performance
- Flame-arrestor is installed to ensure safety



APPLICATION


- UPS
- Telecom
- Golf-Carts
- Cable TV
- Power station
- Marine





SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	88Ah @ 10 hour rate F.V.(1.75V/cell)
Approx. Weight	29.8Kg(65.7lbs.)
Terminals	B3 (Fitting M6 bolt & nut) I2 is optional
Internal Resistance	≤4mΩ (Fully Charged)
Max. Discharge Current	800 A (5 sec.)
Max. Charge Current	26.4 A
Cold Cranking Amp @ -18°C	780 A
Short Circuit Current	2450 A
Operating Temperature Range	Charge : 0°C~50°C(32°F~122°F) Discharge : -20°C~60°C(-4°F~140°F) Storage. : -20°C~50°C(-4°F~122°F)
Container Material	PP: UL 94-HB






ISO 9001  

ISO14001 

UL  MH19884

CE  C4M20310-2474-E-16

- IEC60896
- JIS C 8704
- GB/T 19638

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> ■ Length: 306±2.0 (12.05±0.08) ■ Width: 173±2.0 (6.81±0.08) ■ Container Height: 200±2.0 (7.87±0.08) ■ Total Height: B3:230±2.0 (9.06±0.08), I2:207±2.0 (8.15±0.08) 	  	<p>Terminal I2: </p> <p>Terminal B3: </p> <p>Terminal Hardware Initial Torque: B3,I2(5.5Nm±5%)</p>

Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	20 Min	25 Min	30 Min	40 Min	50 Min	60 Min	90 Min
1.80V		3117	2291	1903	1591	1379	1211	975	818	709	504
1.75V		3494	2459	2013	1653	1420	1242	995	835	720	512
1.70V		3726	2560	2082	1696	1448	1262	1009	845	728	518
1.65V		3878	2639	2129	1728	1471	1276	1021	854	735	522
1.60V		3993	2690	2160	1751	1489	1288	1031	861	741	525

Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	20 Min	25 Min	30 Min	40 Min	50 Min	60 Min	90 Min
1.80V		290	201	165	136	116	101	81	68	59.6	42.3
1.75V		318	217	174	142	121	105	83	70	60.5	43.0
1.70V		339	226	180	146	124	107	85	71	61.2	43.5
1.65V		352	233	185	149	126	109	86	72	61.8	43.9
1.60V		363	237	188	151	128	110	87	72	62.2	44.2

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.