



VRLA Rechargeable Battery

BP17-12



FEATURES

- Maintenance Free (topping up not needed)
- Non - spillable (no free electrolyte)
- Low Self Discharge, less than 3% per month
- both Vertical & Horizontal installations

APPLICATIONS

- UPS
- Switch Boards
- Security Systems
- Medical Equipment
- Laboratory Equipment
- Emergency Lighting



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	17.0Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	6150g(13.56lbs.)
Terminals	B1 (Fitting M5 bolt & nut) , T2 and I1 are optional
Internal Resistance	≤ 16mΩ (Fully Charged)
Max. Discharge Current	255 A (5 sec.)
Max. Charge Current	5.1 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS(UL94 HB) BP17-12 Optional: Flame Retardant ABS(UL94 V-0) BP17-12FR

UL[®]
MH19884

CE

- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1
- VdS G100078

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> ■ Length 181±1.5 (7.13±0.06) ■ Width 76±1.5 (2.99±0.06) ■ Container Height 166±1.5 (6.54±0.06) ■ Total Height 166±1.5 (6.54±0.06) 		<ul style="list-style-type: none"> ● Terminal B1 ● Terminal T2 ● Terminal I1 <p style="text-align: center;">Terminal Hardware Initial Torque: B1(2.5Nm±5%),I1(4.0Nm±5%)</p>

Constant power discharge characteristics at 25 °C/77 °F						Unit: W				
Discharge Time F.V.	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr	
10.8V	615	452	363	216	123.7	49.6	34.2	19.09	10.05	
10.5V	711	490	379	224	127.4	50.5	34.7	19.38	10.20	
10.2V	756	508	391	229	129.7	51.0	34.9	19.48	10.25	
9.9V	790	520	400	232	131.3	51.4	35.0	19.54	10.28	
9.6V	816	530	408	235	132.6	51.7	35.1	19.54	10.28	

Constant current discharge characteristics at 25 °C/77 °F						Unit: A				
Discharge Time F.V.	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr	
10.8V	55.37	39.83	31.53	18.28	10.40	4.129	2.847	1.591	0.837	
10.5V	65.27	43.15	32.98	18.98	10.71	4.212	2.890	1.615	0.850	
10.2V	69.35	44.70	34.00	19.41	10.90	4.250	2.906	1.623	0.854	
9.9V	72.46	45.77	34.78	19.68	11.03	4.280	2.916	1.628	0.857	
9.6V	74.86	46.69	35.48	19.88	11.14	4.305	2.925	1.628	0.857	

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained herein.

For operation, please refer to the instruction from technical manual.

B/4 REV. May. 2021

Powered by **B.B. Tech(Changsha)Co., Ltd.**