

## VRLA Rechargeable Battery

# EVP35-12 Standard Type



### FEATURES

- Absorbent Glass Mat technology for efficient gas recombination
- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for high power & high cyclic usage


### APPLICATIONS

- UPS
- Wheelchairs
- Lawn Mowers
- Electronic Vehicle
- Golf-Carts
- Electronic Medical Equipment



### SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	35Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	12.5Kg(27.571lbs.)
Terminals	B7 (Fitting M6 bolt & nut)
Internal Resistance	≤6mΩ (Fully Charged)
Max. Discharge Current	525 A (5 sec.)
Max. Charge Current	10.5 A
Operating Temperature Range	Charge 0°C~40°C(32°F~104°F) Discharge -20°C~50°C(-4°F~122°F) Storage. -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS( UL94 HB) EVP35-12 Optional: Flame Retardant ABS(UL94 V-0) EVP35-12FR



DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> <li>■ Length 195±1.5 (7.68±0.06)</li> <li>■ Width 129±1.5 (5.08±0.06)</li> <li>■ Container Height 155±1.5 (6.10±0.06)</li> <li>■ Total Height 179±2.0 (7.05±0.08)</li> </ul>		<ul style="list-style-type: none"> <li>● Terminal B7</li> </ul> <p>[M6 BOLT &amp; NUT]</p> <p>Terminal Hardware Initial Torque: B7(5.5Nm±5%)</p>

Constant power discharge characteristics at 25 °C/77 °F										Unit: W
F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V		1503	1065	766	481	274	111.4	70.4	39.2	20.5
1.75V		1740	1154	810	500	282	114.1	71.6	40.0	21.0
1.70V		1849	1200	834	511	289	115.0	72.1	40.3	21.1
1.65V		1933	1227	856	519	292	116.1	72.5	40.3	21.1
1.60V		1997	1249	871	525	294	116.5	72.7	40.3	21.1

Constant current discharge characteristics at 25 °C/77 °F										Unit: A
F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V		139.20	96.83	72.59	42.59	23.06	9.28	5.87	3.27	1.71
1.75V		164.19	105.89	76.94	44.21	23.73	9.51	5.97	3.33	1.75
1.70V		174.47	110.12	79.18	45.19	24.27	9.59	6.01	3.35	1.76
1.65V		182.35	112.53	80.99	45.90	24.53	9.68	6.04	3.36	1.76
1.60V		188.36	114.57	82.44	46.46	24.73	9.71	6.06	3.36	1.76

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.

For operation, please refer to the instruction from technical manual.

B/2 REV. May, 2021

Powered by **B.B. Tech(Changsha)Co., Ltd.**